

Audio/Video applications  
(see p. 751)

# horizontal and vertical cabling

configure your LCS<sup>2</sup> system (continued)

## SELECT RJ 45 SOCKETS AND WI-FI MOSAIC ACCESS POINTS (p. 728-729, 732-733, 737, 748)

				LCS <sup>2</sup> cat. 6A	LCS <sup>2</sup> cat. 6	LCS <sup>2</sup> cat. 5e
	1 module	STP	White	0 765 73	0 765 63	-
		UTP	White	-	0 765 61	0 765 51
	2 modules	STP	White	0 765 76	0 765 66	-
		UTP	White	-	0 765 64	0 765 54
	2 modules with 45° inclined	STP	White	0 765 08	0 765 03	0 765 01
		UTP	White	0 765 09	-	-
	With controlled access	STP	White	0 765 99	0 765 96	-
		UTP	White	-	0 765 94	0 765 97
	Sockets at 90°	STP	White	-	0 765 93	-
		UTP	White	-	0 765 91	-
	Antimicrobial	STP	White	-	0 765 83	-
		UTP	White	-	0 765 81	-
	2 x RJ 45 sockets	UTP	White	-	0 765 44	0 765 41
	Green shutter	STP	White	0 765 24	-	-
		UTP/FTP	White	-	0 765 22	-
	Orange shutter	STP	White	0 765 25	-	-
UTP/FTP		White	-	0 765 23	-	
Copper feedthroughs	UTP	White	-	0 786 22	0 786 20	
Doubler sockets	Ethernet/Ethernet	UTP	0 765 38	0 765 38	0 765 38	
	Telephone/Ethernet	UTP	0 765 36	0 765 36	0 765 36	
	Telephone/telephone		0 765 35	0 765 35	0 765 35	
Manageable Wi-Fi access points	With RJ 45 socket, dual-band and dual-radio		0 779 14	0 779 14	0 779 14	
	Dual-band and dual-radio		0 779 13	0 779 13	0 779 13	

## SELECT 19" LCS<sup>2</sup> FEEDTHROUGH PANELS (p. 758)

	Metal, 2 axes, quick-fixing	1 U	0 465 22
		2 U	0 465 23
	Plastic with brushes, direct clipping	1 U	0 465 28
		2 U	0 465 29
	Metal with brushes, quick-fixing	1 U	0 465 30
		2 U	0 465 31

## 19" POWER DISTRIBUTION UNITS (PDU) (p. 759)

	PDU 2P+E - 2 U	9 x 2P+E sockets	French standard	0 465 50
			German standard	0 465 60
		12 x C13 sockets		0 465 51
		9 x C19 sockets		0 465 52
		6 x 2P+E sockets	French standard	0 465 54
			German standard	0 465 62
		6 x 2P+E sockets Switch with indicator	French standard	0 332 88
		6 x 2P+E sockets Circuit breaker	French standard	0 332 37
			German standard	0 332 38
		6 x 2P+E sockets Tamperproof (UPS)	French standard	0 332 87
		5 x 2P+E sockets	British standard	6 339 00
6 x 2P+E sockets	British standard	0 465 65		
PDU with surge protector - 2 U	6 x 2P+E	0 332 78		
PDU to be equipped - 2 U	Takes 16 Mosaic modules	0 332 79		
DIN rail kit IP 2X - 2 U	For modules appliances	0 465 45		

Red catalogue numbers: New products